

# 50" PDP-502MXE

PROFESSIONAL PLASMA DISPLAY



Pictured With Optional Table Top Stand (PDK5001)

Clean, sharp, **high resolution** image reproduction for video or computer generated data and graphics

- Large 50" screen
- True XGA compatibility for pixel perfect image reproduction
- Wide screen - 16.9 aspect ratio
- New waffle rib structure for better pixel efficiency, outstanding brightness and stunning picture quality
- Black stripe screen for improved contrast
- RS-232 control interface and built-in integrator mode
- Wide range of mounting brackets and stands



**Pioneer**

[www.pioneer-plasma.com](http://www.pioneer-plasma.com)


MacRent

Birger Jarlsg 108

114 20 Stockholm


<http://www.macrent.se>

## Dimensions



## PDP-502MXE Specifications

### Terminal Configuration



### Specifications

Effective Screen Size (W x H)	1098.2 x 620.5 mm (50" Diagonal)
Aspect Ratio	16:9
Number of Pixels	1280 (Hor) x 768 (Ver)
Pixel Pitch	0.858 mm (Hor/RGB trio) x 0.808 mm (Ver)
Colour Resolution	256 Grey Scale 16.7 Million Colours
Brightness	560 cd/m <sup>2</sup> (White Peak)
Contrast Ratio	560:1 (Dark Environment)
Viewing Angle	More Than 160° (Hor) - 160° (Ver)
Dimensions (W x H x D)	1218 x 714 x 98 mm
Weight	40.3 kg
Power Consumption	470W (0.6W At Stand By)
Power Requirements	AC100 - 240V ±10%, 50/60Hz
Operating Temperature	0°C - 40°C
Operating Humidity	20 - 80%
Operating Atmospheric Pressure	0.8 - 1.1 Atmospheric Pressure
Safety Regulation	CE

### Input Signal Compatibility

TV Standard	PAL / NTSC / SECAM / HDTV
-------------	---------------------------

### Input / Output Terminals

Standard Display		Optional Video Box (PDA-5001)	
Signal	Connector	Signal	Connector
Analogue RGB	D-Sub 15 Pin (Input / Output)	Composite / RGB	Scart 1
Component* / RGB	BNC	Composite / Y/C	Scart 2
RS-232	D-Sub 9 Pin	Composite	BNC (Input / Output)
Combination	Mini-Din 6 Pin (Input / Output)	Y/C	BNC
Control	Mini Jack (Input / Output)	S-Video	S-Video Jack
Audio	Stereo Mini Jack / Pin Jack (Input)	Audio	Pin Jack (Input x 2)
Audio	Stereo Mini Jack (Output)		
	Speaker L/R (Output)		

\* Component Signal is only accepted when the Video Box (PDA-5001) is connected

### Personal Computer Input Compatibility

Standard Display	VGA / SVGA / XGA* / Compressed SXGA* and UXGA*
------------------	--

\* 16:9 Graphics Card Required

### Accessories

Accessories Included		Optional Accessories	
Remote Control Unit	x 1	Video Box (PDA-5001)	
Remote Control Unit Case	x 1	Side Mount Speakers (PDP-S04-LR)	
AA(R6) Battery	x 2	16:9 Graphics Card PCI (PDK-GCP2PCI)	
Speed Clamp	x 2	16:9 Graphics Card AGP (PDK-GCP2AGP)	
Bead Band	x 2	Table Top Stand (PDK-5001)	
Tabletop Stand	x 2	Ceiling Bracket (PDK-5002)	
Washer	x 4	Wall Bracket (PDK-5005)	
Hex Bolt	x 2	Tilting Wall Bracket (PDK-5006E/WL)	
Cleaning Cloth	x 1		
Operation Manual	x 1		

Design and specification subject to change without notice. All product names and company names are registered trademarks of their respective owners. Published by Pioneer Europe N.V. Multimedia Division. Copyright 1999 by Pioneer Europe N.V. All rights reserved.

PLASDATA502-BR-SW



**Pioneer**

Pioneer Scandinavia AB  
 Nyckelvägen 2  
 142 82 Trångsund  
 Sweden

Tel: +46 (0) 8 609 91 00  
 Fax: +46 (0) 8 771 10 15

E-mail: multimedia@pioneer.se  
 www.pioneer.se

**MacRent**

Birger Jarlsg 108  
 114 20 Stockholm  
<http://www.macrent.se>